

Parameter		Value
Physical Parameter	Pixel Configuration	DIP570
	Pixel Pitch (mm)	8
	Pixel matrix per panel	120x120
	Pixel density (pixels/sq.m.)	15625
	Cabinet Dimensions (LxWxH)/ (mm)	960X960X 168
	Module Dimensions (LxWxH)/ (mm)	320X160X26.9
	Panel material	Iron
	Cabinet weight (kg/panel)	47
	Module weight (kg/panel)	0.87
Electronic Parameter	Color Grayscale (Bit)	14bit
	Gray Scale per Color (level)	16384
	Refresh Rate (Hz)	1560
	Driving Type	1/4
	Signal Transmission Distance (m)	CAT5 cable: <100 m; Single mode fiber: <10 km
Optical Parameter	Brightness (nit)	8000/10000(FCC,CE,ETL)
	Optimal Horizontal Viewing Angle (°)	100
	Optimal Vertical Viewing Angle (°)	100
Electrical Parameter	AC Input Voltage (V)	AC: 100-240V±10%
	AC Input Frequency (Hz)	50
	AC Input Power Maximum Value (W/m ²)	445/551(FCC,CE,ETL)
	AC Input Power Typical Value (W/m ²)	148/182(FCC,CE,ETL)
Circumstance Parameter	Storage Temperature (°C)	-40 -70
	Working Temperature (°C)	-20 -50
	IP rating (Front/Rear)	IP65/IP54
	Storage Humidity (RH)	10%~90% non-condensing
	Working Humidity (RH)	10%~60% non-condensing
	Lifetime Typical Value (hrs)	100000
Installation Type	Cabinet installation type	Fix
	Rigging Quantity (Vertical) (PCS)	\



